

### DEPARTMENT OF PLANNING & BUILDING 250 FRANK H. OWAGA PLAZA. SECOND FLOOR, OAKLAND CA. 94612

# COMPLIANCE WITH STATE LAW SB407 RELATING TO WATER SAVING PLUMBING FIXTURES

### Regulations for Plumbing Fixture Replacement in Existing Single-Family Residential and Multi-Family Residential and Commercial Buildings

As of January 1, 2014, SB 407 requires non-compliant plumbing fixtures to be replaced with water-conserving plumbing fixtures when a property is undergoing additions, alterations or improvements. Applicants seeking to obtain permits for any of these types of work will be required to replace non-compliant fixtures prior to final permit approval or issuance of a certificate of occupancy by the local building department. This law applies only to properties built on or before January 1, 1994.

Per Civil Code Section 1101.4, for any single-family residential real property, on and after January 1, 2014, building addition, alteration or improvement will require all non-compliant plumbing fixtures to be replaced with water-conserving plumbing fixtures. **On or before January 1, 2017**, all non-compliant plumbing fixtures shall be replaced with water-conserving plumbing fixtures (<u>regardless of whether property undergoes alterations or improvements</u>).

Per Civil Code Section 1101.5, for any multifamily residential real property and any commercial real property, on and after January 1, 2014, specified building addition, alteration or improvement will require non-compliant plumbing fixtures to be replaced with water-conserving plumbing fixtures. **On or before January 1, 2019**, all non-compliant plumbing fixtures shall be replaced with water-conserving plumbing fixtures (<u>regardless of whether property undergoes alterations or improvements</u>).

#### Interpretation for Duplex (Two-Family Dwelling) and Second Unit

Civil Code Section 1101.3 defines "single-family residential real property" as any real property that is improved with, or consisting of, a building containing not more than one unit that is intended for human habitation. It also defines "multifamily residential real property" as any real property that is improved with, or consisting of, a building containing more than one unit that is intended for human habitation.

To maintain consistency with the scope and application of the building and residential code, for purposes of applying Civil Code Sections 1101.1 through 1101.8, a real property consisting of a duplex (two-family dwelling) will be considered a single-family residential real property. Alterations to one dwelling unit will trigger plumbing fixture upgrades within that unit only and not the adjacent unit.

A real property consisting of a single-family residence with either a detached or attached second unit will also be considered a single-family residential real property. Alterations to the residence will trigger plumbing fixture upgrades within the residence only and not the second unit, and vice versa.

#### Clarification of "Non-Compliant Plumbing Fixture"

Please note that according to the definition of "non-compliant plumbing fixture" in Civil Code Section 1101.3(c), the existing plumbing fixture water usage/flow rate must **exceed** the amount shown to be considered non-compliant. If the existing plumbing fixture water usage/flow rate is equal to or lower than the amount shown, it is not required to be upgraded.

#### **Code Reference(s):**

- Senate Bill 407 (2009) / California Civil Code Sections 1101.1 through 1101.8
- 2013 California Green Building Standards Code (CALGreen) Section 301



# DEPARTMENT OF PLANNING & BUILDING 250 FRANK H. OWAGA PLAZA. SECOND FLOOR. OAKLAND CA. 94612

### Water-Conserving Plumbing Fixtures Certificate of Compliance by Property Owner

Owner Nam		e	Permit No			
Аp	plicant Na	ame				
Ad	dress					
		PERMIT CANNOT BE FINALED AND CO HAS BEEN <u>SIGNED</u> AND <u>RETURN</u>				
Ple	ase refer to	to the attached California Civil Code Sections 1101.	1-1101.8 which are part of this Certification form.			
1.	Is your re  ☐ Yes.	Is your real property a registered historical site?  ☐ Yes. Civil Code Sections 1101.1 through 1101.8 do not apply. Sign below and skip the rest of the form.				
	□ No.	Owner/Applicant's SignatureGo to Question 2.	Date			
2.		g, installation of water-conserving plumbing fixture	not apply.			
	□ No.	Owner/Applicant's SignatureGo to Question 3.	Date			
3.	Is water s  ☐ Yes.	service permanently disconnected for your building Civil Code Sections 1101.1 through 1101.8 do	? not apply. Sign below and skip the rest of the form.			
	□ No.	Owner/Applicant's SignatureGo to Question 4.	Date			
		My real property is built and available for use of				
		Owner/Applicant's Signature	Date			
		fixtures to be replaced with water-conserving p On or before January 1, 2017, all non-complian plumbing fixtures (regardless of whether prope My property is a <i>multifamily residential</i> real prope	oly. Refer to the attached. Deerty. See Civil Code Section 1101.4. Deerty. See Civil Code Section 1101.4. Deerty. See Civil Code Section 1101.4. Deerty. See Civil Code Section 1101.5. Deerty. See Civil Code Section 1101.5. Deerty alterations or improvements shall require non-compliant			

On or before January 1, 2019, all non-compliant plumbing fixtures shall be replaced with water-conserving plumbing fixtures throughout the building (regardless of whether property undergoes alterations or improvements).

☐ My property is a *commercial* real property. See Civil Code Section 1101.5.

On and after January 1, 2014, specified building alterations or improvements shall require non-compliant plumbing fixtures to be replaced with water-conserving plumbing fixtures.

On or before January 1, 2019, all non-compliant plumbing fixtures shall be replaced with water-conserving plumbing fixtures throughout the building (regardless of whether property undergoes alterations or improvements).

I/We, the owner(s) of this property, certify under penalty of perjury that non-compliant plumbing fixtures have been replaced with water-conserving plumbing fixtures in accordance with Civil Code Sections 1101.1 through 1101.8, the current California Plumbing Code and California Green Building Standards Code, and manufacturer's installation requirements, and that the water-conserving plumbing fixtures comply with the requirements as indicated in the table below.

Owner/Applicant's Signature Da	ite
--------------------------------	-----

Upon completing and signing this Certificate, please return it to the Building Division in order to final your permit.

	Non-Compliant Plumbing Fixture <sup>1</sup>	Water-Conserving Plumbing Fixture (Fixture Complying with Current Code Applicable to New Construction)				
<b>F</b> '		Maximum Water Usage/Flow Rate				
Fixture Type	Water Usage /Flow Rate	2013 CPC Ch. 4 2013 CALGreen Div. 4.3 Single-Family	2013 CPC Ch. 4 2013 CALGreen Div. 4.3 <b>Multifamily</b>	2013 CPC Ch. 4 2013 CALGreen Div. 5.3		
		Residential	Residential	Commercial		
Water Closets (Toilets)	Exceed 1.6 gallons/flush	Single flush toilets: 1.28 gallons/flush Dual flush toilets: 1.28 gallons/flush effective flush volume (the composite, average flush volume of two reduced flushes and one full flush)				
Urinals	Exceed 1.0 gallon/flush	0.5 gallons/flush				
Showerheads  Exceed 2.5 gallons per minute @ 80 psi. Also certified to the performance criteria o EPA WaterSense Specification for Showerheads (A hand-held shower is considered a showerhead.)  For multiple showerheads serving one shower, the combined flow rate of all showerheads and/or other shower outlets controlled by a single valve shall no exceed 2.0 gallons per minute @ 80 psi, or the shower shall be designed to a only one shower outlet to be in operation at a time.						
Faucets – Lavatory Faucets	Exceed 2.2 gallons per minute	Maximum 1.5 gallons per minute @ 60 psi; minimum 0.8 gallons per minute @ 20 psi	Within units: Maximum 1.5 gallons per minute @ 60 psi; minimum 0.8 gallons per minute @ 20 psi  In common and public use areas: 0.5 gallons per minute @ 60 psi	0.5 gallons per minute @ 60 psi		
Faucets – Kitchen Faucets	Exceed 2.2 gallons per minute	1.8 gallons per minute @ 60 psi May temporarily increase up to 2.2 gallons per minute @ 60 psi, and must default to maximum 1.8 gallons per minute @ 60 psi Where faucets meeting the above are unavailable, aerators or other means may be used to achieve reduction.	1.8 gallons per minute @ 60 psi May temporarily increase up to 2.2 gallons per minute @ 60 psi, and must default to maximum 1.8 gallons per minute @ 60 psi Where faucets meeting the above are unavailable, aerators or other means may be used to achieve reduction.	1.8 gallons per minute @ 60 psi		